

z - Anchors, Expanding and Plate

DISTRIBUTION

Designated Maximum holding power-lbs.		6,000	8,000	10,000	12,000
Min. Area (sq. in.)		90	100	120	135
Rod Dia. (inch ³ / ₄)		³ / ₄	⁵ / ₈	³ / ₄	³ / ₄
Rod Length (feet)		7	7	8	-
	<u>Type</u>				
Grip-Tite	8 way	A322812G	A322812G	A322812G	A322812G
Hubbell (Chance)	8 way	88135	88135	88135	88135
MacLean Power Systems	8 way	-	J8115	J8135	J8135
Line Hardware	8 way	8-100G	8-115G	8-135G	8-135G

NOTE: Where galvanized anchors are listed, the same anchors ungalvanized (black asphalt coated) are also acceptable.

z - Anchors, plate

Applicable Specification "RUS Specification for Steel Plate Anchors," T-3

TRANSMISSION

Minimum Area 400 sq. in.

3/4" Galv. Rods

<u>Grip-Tite</u>	XP24 - 3/4 - G
Hubbell (Chance)	X24 - 3/4
<u>MacLean Power Systems</u>	J3524 - 3/4
<u>Line Hardware</u>	CP-24G

NOTE: Where galvanized anchors are listed, the same anchors ungalvanized (black asphalt coated) are also acceptable.

z - Anchors, Service

Designated Maximum Holding Power in Sand - 2500 lbs.

	<u>Screw</u>	<u>Expanding</u>
Eritech (Carolina Galvanizing)	86346606	-
Grip-Tite	-	322065G
Hubbell (Chance)	6346	6870
MacLean Power Systems	J6526W-CA	JO870
Line Hardware	-	8-70G

z - Anchors, Swamp

DISTRIBUTION

10" dia. 12" dia. 15" dia.

MacLean Power Systems	D-6710-S	D-6713-S	D-6715-S
Foresight	-	MR-SR*	-
Hubbell (Chance)	C1101169	C1101170	C1101171

*Drive type anchor. Surface area meets or exceeds that of 12" diameter anchors.

NOTE: Where galvanized anchors are listed, the same anchors ungalvanized (black asphalt coated) are also acceptable.

x – Rod, anchor

Applicable Specification: ANSI C135.2, "Standards for Galvanized Ferrous Strand Eye Anchor Rods"

Applicable Sizes:

- Single guy: 5/8 inch diam. 6, 7 and 8 ¾t long
3/4 inch diam. 8, 9 and 10 feet long
1 inch diam. 9 and 10 feet long
- Double guy: 5/8 inch diam. 7 and 8 ¾t long
3/4 inch diam. 8, 9 and 10 feet long
1 inch diam. 9 and 10 feet long
- Single Guy: Drive: 5/8 inch diam. 7 and 8 ¾t long
3/4 inch diam. 8, 9 and 10 feet long
1 inch diam. 9 and 10 feet long
- Double Guy: Drive: 5/8 inch diam. 7 and 8 ¾t long
3/4 inch diam. 8, 9 and 10 feet long
1 inch diam. 9 and 10 feet long

The following manufacturers have shown compliance with the applicable specifications. Some manufacturers cannot supply all sizes listed above. Check with manufacturer or distributor for availability.

- Allied Bolt, Inc.
- Dixie
- Eritech (Carolina Galvanizing/Knight)
- Grip-Tite
- Hubbell (Chance)
- Joslyn
- Kortick
- Utilities Service

Conditional List
x(1)
July 2009

x – Rod, anchor

Applicable Specification: ANSI C135.2 "Standards for Galvanized Ferrous Strand Eye Anchor Rods" except rods are copper covered. Copper coating thickness is **13 mils minimum** at any point and a 15 mil average. All purchases should specify that a factory certification to the thickness of the copper must accompany the shipment of the rods.

Applicable Sizes: Dou³/₄ Guy – 3/4 inch diameter, 8 and 9 feet long.

<u>Manufacturer</u>	<u>Conditions</u>
Joslyn	<ol style="list-style-type: none">1. To obtain experience.2. For transmission purposes only.3. For use with log anchors or copper covered plate anchors only.4. To be used with copper coated hardware or bronze hardware underground.

Conditional List
x(2)
July 2012

x – Rod, anchor

Applicable Specification: ANSI C135.2 "Standards for Galvanized Ferrous Strand Eye Anchor Rods" except rods are copper covered. Rods meet UL-465 specification for copper coating thickness of **10 mils minimum** at any point. All purchases should specify that a factory certification to the thickness of the copper must accompany the shipment of the rods.

Applicable Sizes: Double Guy – 3/4 inch diameter, 8 and 9 feet long.

Manufacturer

Conditions